

A Compact Rig with **Dynamic Performance**

The A200 R HDD is designed to work in narrow streets. The 65 HP Ashok Leyland engine delivers unmatched performance that operators can feel and appreciate during tough pull back conditions. The A200 R features a high quality rack-pinion system with a thrust/pullback capacity of 10 tons. The A200 R delivers a torque of 4900 Nm that provides high performance, greater crew productivity and efficiency. The A200 R features sealed and lubricated track rollers, carrier rollers and idlers that provide long service life, which keeps your machine in the field and working longer.



Apollo single piece forged drill rod provides the optimal range of strength and more flexibility with finished threads.



A200R HDD











India's First Horizontal
Directional Drill (HDD) Machine



Technical Specifications

Dimensions & Weights		
Length	5250 mm	
Width	1575 mm	
Height	2020 mm	
Weight (without drill pipe)	4940 kg	
Weight (with drill pipe)	5598 kg	
Travelling Speed	1.50 km / hour	
Engine		
Make & Model	Ashok Leyland AL H3CTIC3R23 BS III	
Fuel Type	Diesel	
Maximum Engine Speed	2300 RPM	
Number of Cylinders	3	
Horse-Power Rating	65 HP	
Maximum Torque	245 Nm @ 1900 RPM	
Drill Pipe		
Length	3048 mm (3 m)	
Weight (Each Pipe)	23.5 kg	
Rod Box Capacity	28 Pipes	
Minimum Bend Radius	100 feet	
Pipe Diameter	54 mm	
Water Pump System		
Flow	100 LPM	
Pressure	1000 PSI	

Technical Parameter		
Maximum Spindle Speed	185 RPM	
Maximum Spindle Torque	4900 Nm	
Minimum Bore Diameter	3.5"	
Thrust Force	9850 kg	
Pull-Back Force	9850 kg	
Features		
Electrical System	12 V	
Drilling Lights	YES	
Stake-Down System (Auto-Anchoring)	YES	
Rack-Pinion System	YES	
Hydraulic Systems		
Auxiliary Pump Relief Pressure	3000 PSI	
Thrust/Pull-Back Pump Relief Pressure	3350 PSI	
Rotational Pump Relief Pressure	3750 PSI	
Fluid Capacities		
Engine Oil Capacity	10 Litre	
Diesel Tank Capacity	120 Litre	
Hydraulic Oil Tank Capacity	182 Litre	

@ ApolloTechno Industries Pvt. Ltd. can change specifications without any prior notice. Accessories shown with product may optional and not a part of standard supply.



Factory :

ApolloTechno Industries Pvt. Ltd.

Survey No. 167, Ahmedabad-Mehsana NH-8, Mandali - 382732, Dist.: Mehsana, (Gujarat) India. info@apollotechno.in | www.apollotechno.in

Global Reach:

Apollo Techno International FZCO

P.Ö. Box 342182, Light Industrial Unit 3, LIU - Phase 3, Warehouse No. A10, Dubai Silicon Oasis, Dubai, UAE. Tel: +971 4 3441085 | Fax: +971 4 3441162 info@apollotechnoint.ae | www.apollotechnoint.ae